

Lignocellulose Fiber Filler For Thermoplastic Composite Compositions

by

William W. Jacobsen

Cross-References

none

Government Rights

none

Background

This invention relates generally to a reinforcement filler for thermoplastic composite compositions, and more particularly concerns a discontinuous lignocellulose fiber filler.

The intent of filled, reinforced thermoplastic composite technology is to create new materials and market applications by lowering the cost or improving the physical properties of thermoplastics. The cost and performance of the thermoplastic composites are generally a function of three variables: (1) the cost and performance of the composite materials, (2) the performance of the resultant composite matrix, and (3) the performance of the interfacial bond between the filler material and the thermoplastic material.

The art of incorporating discontinuous cellulose fiber or discontinuous lignocellulose fiber as a filler in thermoplastic resins to create moldable compositions is well known. Such compositions are known to yield moldable composite compositions with improved tensile strength and flexural properties.

Unfortunately, the physical properties of discontinuous cellulose fiber or discontinuous lignocellulose fiber filler have not, as yet, been addressed as a significant factor relative to the properties of the resultant thermoplastic composite. In fact, conventional fiber-filled thermoplastic composite compositions are relatively indiscriminate as to the source of the fiber, deriving the fiber filler from wood flour, wood chips, rice hulls, used paper, pulp, cellulose powder and mixtures thereof. Moreover, where a wood fiber source is used, the selection of

softwood or hardwood to achieve desired end product performance properties is either indiscriminate or unnecessarily specific.

There is some evidence that the physical properties of the fiber filler and resultant thermoplastic composite vary as the source of fiber varies. For example, it is known that the Modulus of Rupture (MOR), a measure of composite brittleness, of discontinuous lignocellulose fiber thermoplastic composites is primarily a function of the source and nature of the discontinuous lignocellulose fiber. Specifically, using discontinuous lignocellulose fiber derived from chemically unaltered (hereafter referred to as "virgin") wood leads to thermoplastic composites possessing significantly higher MOR properties than thermoplastic composites filled with fiber from non-virgin or non-wood cellulose sources.

Further, discontinuous cellulose and lignocellulose fibers commonly used in thermoplastic composites are fine fibers, typically referred to as "wood flour" or "dust". However, longer discontinuous lignocellulose fibers have the capacity to withstand greater stress, and thus have greater tensile properties than shorter fibers of a similar nature. Under load, tensile stress transferred from the composite matrix to the fiber increases from zero at the end of fiber to a maximum value at the fiber's center. As the fiber length increases, the surface area of the fiber increases thereby increasing the distribution of applied stress. As the distributed loading of stress increases over the greater surface area of a longer discontinuous lignocellulose fiber, the amount of stress at a given load at the center of the fiber decreases. Consequently, a longer fiber can absorb greater stress prior to failure than a shorter fiber.

The performance of discontinuous lignocellulose fiber thermoplastic composites is also a function of the concentration of discontinuous lignocellulose fibers in the composite composition. For example, as the pulp wood fiber content in a polypropylene-fiber thermoplastic composite is increased, the tensile and flexural properties of the composition improve until a concentration of 50 percent pulp wood fiber by weight of the composite is reached. Beyond the 50 percent pulp wood fiber loading rate, the tensile and flexural properties of the composite declines.

Related to the concentration of discontinuous lignocellulose fibers in thermoplastic composite compositions is the volume of the fiber in the composite. Fiber volume is a function of the size of the discontinuous lignocellulose fiber and the density of the fiber. Fiber density is

determined by the density of the tree species selected as the source of the fiber. At a given length and density, a fiber with a greater diameter will weigh more than a small diameter fiber of similar nature proportionate to the change in the fiber's surface area. However, as the weight of the individual fibers increases, the number of fibers at a given concentration in a thermoplastic composite composition decreases. This decrease of discontinuous lignocellulose fibers within the discontinuous lignocellulose fiber thermoplastic matrix reduces the number of discontinuous lignocellulose fiber and thermoplastic interfaces, which has the same effect as lowering the concentration of the discontinuous lignocellulose fibers in the composite resulting in a composite with reduced tensile and flexural performance.

Coupling agents are usually needed to improve the interfacial bond between the wood fibers and thermoplastic. The coupling agent effectively creates a bridge between the fibers and the thermoplastic which improves the tensile and flexural properties of the thermoplastic composite under load. However, the use of coupling agents adds to the cost of manufacturing the composite composition.

For the foregoing reasons, there is a need for an improved discontinuous lignocellulose fiber filler for thermoplastic composite compositions. The discontinuous lignocellulose fiber should include a relatively high percentage of long fibers to create a large surface area for interface between the fiber and the thermoplastic. The concentration of the new discontinuous lignocellulose fiber in the composite composition should yield increased tensile strength and flexural properties in the composite composition. The tensile and flexural properties of the composite product should improve as the percentage of long fibers are increased. Ideally, the source of the composite materials and manufacturing the discontinuous lignocellulose fiber and the composite composition are simple and cost effective.

Summary

The present invention is a discontinuous lignocellulose fiber that satisfies these needs. A discontinuous lignocellulose fiber filler for thermoplastic compositions having features of the present invention includes a significant percentage by weight of long, "hair-like" fibers. Preferably, at least about 20 percent by weight of the fiber filler is discontinuous lignocellulose fiber with a fiber length greater than about 15 millimeters and a fiber diameter less than about 0.5

millimeters. A thermo-mechanical process is used for producing the subject discontinuous lignocellulose fiber, comprising the steps of conditioning wood chips under about 80 to about 100 psi of steam pressure for a period of about one to about four minutes, and mechanically separating the chips into individual discontinuous fibers.

A moldable thermoplastic composite composition including the discontinuous lignocellulose fiber of the present invention comprises about 20 to about 50 percent by weight of the fiber filler and about 50 to about 80 percent by weight thermoplastic. Optionally, the thermoplastic composite composition may further comprise up to about 10 percent by weight of a coupling agent. The composition is prepared by a process comprising the steps of blending the discontinuous lignocellulose fiber, thermoplastic, and coupling agent or other additives, extruding the blended materials at an extruder operating temperature of less than about 450°F, and forming the extruded composites into finished products by profile extrusion, cold compression molding, hot compression molding or injection molding.

Accordingly, it is an object of the present invention to provide a new discontinuous lignocellulose fiber for thermoplastic composite compositions having one of more of the novel features of this invention as set forth above or hereafter shown or described.

Another object of the present invention is to engineer discontinuous lignocellulose fibers to improve the physical properties of this component of the thermoplastic composite yielding cost effective composites with improved properties over basic thermoplastic. A related object of the present invention is to improve thermoplastic composite strength and stiffness properties by incorporating the new fiber filler, thereby creating compositions with properties suitable for a wide range of market applications that would include, but not be limited to, structural packaging, automotive interior trim, architectural components, furniture components, and the like.

A further object of the present invention is to produce improved thermoplastic composite compositions comprising the new discontinuous lignocellulose fiber filler without the need for coupling or bonding agents or other additives.

A feature of the invention is the size distribution of the discontinuous lignocellulose fiber reinforcing filler, which includes a high percentage by weight of long, hair-like fibers. The size distribution of the fiber as percent by total weight withheld on ASTM screens is about 20 to about 50 percent withheld on an eight mesh screen, about 20 to about 40 percent withheld on a

sixteen mesh screen, about 20 to about 30 percent withheld on a fifty mesh screen, and about 10 percent finer than a fifty mesh screen. The discontinuous lignocellulose fiber is preferably derived from virgin, waste wood from either softwood or hardwood tree species, depending on the end use of the composite component. The thermoplastic can be selected from a number of post-consumer or post-industrial waste sources. Coupling agents are optional, but may be used to further enhance the tensile and flexural properties of the composite compositions.

The discontinuous lignocellulose fiber reinforcement filler of the present invention, when incorporated into thermoplastic composites at concentrations of at least about 20 percent by weight, improves the tensile and flexural properties of the thermoplastic and yields composite compositions with improved stiffness and strength properties. Moreover, the improved fiber filler and composite may be prepared using conventional manufacturing equipment and from wood waste and recycled thermoplastic thereby minimizing materials and manufacturing costs.

These and other features, objects and advantages of the present invention will become apparent with reference to the following description and appended claims.

Description

A discontinuous lignocellulose fiber is described for use as a reinforcing filler in thermoplastic composite compositions. The lignocellulose fiber of the present invention is derived from a virgin wood source using a thermo-mechanical process which yields a fiber filler having a predetermined size distribution, including a high percentage by weight of long, "hair-like" fibers. The discontinuous lignocellulose fiber filler is blended with thermoplastic and extruded to produce a composition having improved physical properties. A coupling agent may be used to improve the interfacial bond between the fiber and thermoplastic.

In accordance with the present invention, the source of the discontinuous lignocellulose fiber is a significant factor. Chemically unaltered, or "virgin", wood is the preferred source since, as discussed above, the MOR of the molded thermoplastic composite is enhanced. The virgin wood source may be either softwood or hardwood, depending on the desired composite performance properties. Softwood is preferred for composite applications requiring greater impact resistance, such as packaging and the like. Hardwood is preferred for applications requiring greater strength or stiffness, such as office chair seat backs and the like. Southern Pine

and Poplar are the preferred representatives from the softwood and hardwood groups, respectively, due to lower cost and availability. However, within their respective groups, other tree species such as, but not limited to, Aspen, Birch, Cottonwood, Douglas Fir, Oak, Spruce, Loblolly Pine, and others are suitable for use as the fiber source in the present invention.

The preferred virgin wood source of Southern Pine or Poplar is wood waste, such as discarded pallets, furniture manufacturing scraps and the like. The primary reason is that wood waste has usually been previously air or kiln dried to a moisture content that ranges from about 7 to about 12 percent by weight. This is close to the typical moisture content for discontinuous lignocellulose fiber as a component of a thermoplastic composite of about 5 percent or less by weight. Composite compositions containing discontinuous lignocellulose cellulose fiber with moisture contents in excess of 5 percent by weight often yield molded products having visually unappealing blisters. Blistering is a result of conversion of the moisture within the fiber into steam during the extrusion step of the composite production process. Further, green wood mill chips have a moisture content which ranges from about 45 to about 50 percent by weight. Thus, drying wood waste to the appropriate moisture control content requires less energy than drying green wood mill chips, which decreases processing cost.

The discontinuous lignocellulose fiber filler of the present invention comprises a significant percentage by weight of long fibers, preferably exceeding about 15 millimeters. I have observed that as the concentration of long fibers in a thermoplastic composite composition increases, the tensile and flexural properties of the composite improve, regardless of tree species.

The preferred diameter of the long discontinuous lignocellulose fibers is between about 0.1 and about 0.5 millimeters. In this diameter range, the distribution of the discontinuous lignocellulose fibers in the discontinuous lignocellulose fiber thermoplastic composite matrix is optimized. Utilizing fibers with diameters in excess of about 0.5 millimeters is not desirable since, at a given length and weight concentration in the composite, the volume of discontinuous lignocellulose fibers would be reduced. For example, the volume of discontinuous lignocellulose fibers measuring one millimeter in diameter would be approximately one half that of fibers measuring 0.5 millimeters in diameter. This would reduce the number of fiber and thermoplastic interfaces by approximately 50 percent and result in a composite with decreased tensile and flexural performance. Moreover, to increase the weight concentration of a one millimeter

diameter fiber to achieve comparable distribution properties in the composite to that of a smaller diameter fiber would result in a heavier composite composition. However, in many applications, such as automotive interior trim, it is undesirable to add weight to the end product.

A thermo-mechanical pulp process is used to derive the discontinuous lignocellulose fiber to achieve the preferred size distribution in the fiber filler. Thermo-mechanical fiber separation is preferred over mechanical fiber separation methods, such as hammer milling or stone grinding, because such mechanical fiber separation methods are incapable of producing the present invention's discontinuous lignocellulose fiber size distribution.

A suitable thermo-mechanical pulp process for preparing discontinuous lignocellulose fiber, particularly long, hair-like discontinuous lignocellulose fiber, is taught by the present inventor in U. S. Patent No. 5,330,828 which issued July 19, 1994, the contents of which are hereby incorporated by reference. The process is manipulated, as described below, to achieve a size distribution of discontinuous lignocellulose fibers whereby a significant percentage by weight of the discontinuous lignocellulose fibers have a length which exceeds about 15 millimeters and a diameter of less than about 0.5 millimeters.

In the process, wood chips are conditioned under pressure and mechanically separated into individual discontinuous fiber bundles, herein referred to as "fibers". The conditioning step consists of feeding either hardwood or softwood chips of similar species derived from wood mills or wood waste into a vessel pressurized with steam to between about 80 psi to about 100 psi for a period of about one to about four minutes. Residence time in the pressurized vessel for less than about one minute results in poor fiber separation resulting in fibers with diameters in excess of the preferred 0.5 millimeters. Residence time beyond four minutes yields no additional fiber separation benefits while slowing the production process.

The wood chips exit the pressurized vessel via a screw conveyor which is maintained at a pressure of about 65 to about 85 psi. The screw conveyor carries the pressurized wood chips to a Sands Model 36-inch Defibrator refiner where the wood chips are mechanically separated under pressure into individual fibers by passing the pressurized wood chips between a static disc and a rotating disc. The distance between the rotating disc and the static disc is set at about 0.003 inches to about 0.010 inches, with a preferred rotating disc speed of about 1,200 RPM.

Discontinuous lignocellulose fiber produced by this process ranges in length from a few microns to about 30 millimeters, and in diameter from a few microns to about two millimeters. The resultant size distribution of the discontinuous lignocellulose fiber is preferred to be from about 20 to about 50 percent by weight retained on an eight mesh screen, from about 20 to about 40 percent by weight retained on a sixteen mesh screen, from about 20 to about 40 percent by weight retained on a fifty mesh screen and the remaining fiber fine enough to pass through a fifty mesh screen.

The fibers are subsequently dried to a moisture content of about 5 percent by weight. Any suitable dryer is used, such as a Procter and Schwartz gas burner, flash dryer. The discontinuous lignocellulose fiber preferably enters the dryer at a dryer temperature of about 380°F and exits the dryer at a temperature of about 170°F. The discontinuous lignocellulose fiber residence time within the dryer is usually less than about one minute.

The thermoplastic component selected for use in the composite composition of the present invention is selected for its physical properties relative to the desired performance characteristics of the composite composition. The wide array of commercially available thermoplastics, such as polyethylenes, polypropylenes, ABS, and the like, possess different physical properties. For example, per ASTM D638, unfilled general purpose polystyrene has a tensile performance value ranging from 5000 to 8000 pounds per square inch compared to unfilled high density polyethylene with a tensile performance value ranging from 1400 to 4000 pounds per square inch. The notched Izod values of polystyrene per ASTM D256 range from 0.25 to 0.35 foot pounds per square inch compared to high density polyethylene with notched Izod values ranging from 0.4 to 6.0 foot pounds per square inch. Comparatively, polystyrene would be selected over high density polyethylene for applications requiring high strength. Conversely, high density polyethylene would be selected over polystyrene for applications requiring high impact properties.

The thermoplastic component may be derived from recycled or non-recycled thermoplastic sources. It is preferred to utilize recycled or waste thermoplastics due to the lower cost versus non-recycled thermoplastic. It is also desirable that the thermoplastic have a softening or melting temperatures less than about 450°F. Processing the lignocellulose fiber and thermoplastic blend at an extrusion temperature of more than about 450°F could lead to burning

of the discontinuous lignocellulose fiber, which causes the composite compositions to lose their advantageous physical properties. The thermoplastic is prepared according to any conventional method, such as grinding, shredding and pelletizing, and the like. Ideally, the thermoplastic pieces are less than about 1/4 inches in all dimensions.

The steps for processing the component materials to yield the composite include low shear mechanical blending of the discontinuous lignocellulose fiber and thermoplastic and subsequent extrusion followed by profile forming, cold or hot compression molding or injection molding and cooling.

In the blending step, the discontinuous lignocellulose fiber is combined with the thermoplastic component in a low shear mixing device. Low shear devices are preferred in order to minimize discontinuous lignocellulose fiber fracturing and length reduction. The preferred concentration of discontinuous lignocellulose fiber filler in the thermoplastic composite composition of the present invention ranges from about 20 to about 50 percent by weight of the composite, depending on the desired physical properties of the composite. Composite molded products incorporating lignocellulose fiber filler at concentrations outside this range yield negligible tensile and structural property improvements and lose their hybrid properties. Molded products incorporating less than about 20 percent by weight of the discontinuous lignocellulose fiber filler of the present invention are more like the thermoplastic whereas, at concentrations at more than about 50 percent by weight, the products become wood-like, neither of which is a desired characteristic of a reinforced, filled thermoplastic.

Composite products molded from composite compositions prepared according to the present invention demonstrate improved tensile and flexural properties as the concentration of the discontinuous lignocellulose fiber filler increases within the above range. However, it has been observed that as the tensile and flexural properties improved, notched Izod properties declined. Consequently, the concentration of the discontinuous lignocellulose fiber filler in the composite is driven by the requirements of the application of the molded product for either flexibility or rigidity.

Additional components, such as coupling agents, foaming agents, coloring, U.V. stabilizers, and the like, may optionally be added to the composite during or prior to blending. As noted above, coupling agents are used, for example, to enhance the interfacial bond between

the discontinuous lignocellulose fiber and the thermoplastic. When used for interfacial bond improvement in the composite composition of the present invention, the preferred coupling agents include maleated or maleic anhydride grafted polypropylene or polyethylene, ethylene methacrylic or acrylic acid. Maleic anhydride grafted polyethylene is the preferred coupling agent when polyethylene is the base resin of the thermoplastic composite. Maleic anhydride grafted polypropylene is the preferred coupling agent for composite compositions wherein the base resin is polypropylene. Based on the compatibility constraints observed between the maleated polyolefins and the base resin, ethylene methacrylic or acrylic acid is the preferred coupling agent when the base thermoplastic resin is a mixture of polyethylene and polypropylene (common in the use of post-consumer thermoplastic waste) or other thermoplastic resins or mixtures of thermoplastic resins with melting or softening temperatures below about 450°F. This would include, but not be limited to, polyvinyl chloride, polystyrene, polyanimides, polyester, ABS, and the like.

The amount of coupling agent in the composite composition is preferably up to about 10 percent by weight of the composite. Concentrations of the preferred coupling agents in excess of about 10 percent by weight yield little, if any, gain in the performance of the composite.

The compounded material is fed to an extruder. A single or twin screw extruder or a kinetic mixer may be utilized to soften the plastic and mix the composite components. A single screw extruder or kinetic mixer is preferred due to lower shear and less fiber fracturing. A Sterling six-inch bore extruder with a 34:1 screw compression ratio is suitable.

It is important that during extrusion the discontinuous lignocellulose fiber not be subjected to heat which is sufficient to burn the discontinuous lignocellulose fiber. Therefore, the material is preferably extruded at a temperature of between about 350°F and about 450°F, and more preferably between 350°F and 400°F. Extrusion temperatures in excess of 450°F will burn the discontinuous lignocellulose fiber, resulting in deteriorated composite properties. Further, as the temperature of the extruded composite increases, cold compression mold cycle time increases, resulting in lower productivity and higher costs. Extrusion temperatures less than 350°F fail to adequately reduce the viscosity of the thermoplastic, resulting in poor discontinuous lignocellulose fiber mixing and composite distribution. This contributes to a loss of composite tensile strength and flexural properties.

The extruded composite can be shaped into finished parts by a variety of means including, but not limited to, cold compression molding, hot compression molding, profile extrusion, injection molding, and the like. The thermal resistance of the discontinuous lignocellulose fiber of the present invention lowers the temperature of the extruded composite which results in quicker mold cycle times, thereby improving productivity and lowering cost. For example, cold compression molding of a molten extruded composite comprising 30 percent discontinuous lignocellulose fiber by weight of the composite results in mold cycle times that are about 10 to about 20 percent faster than those of the thermoplastic without the fiber filler.

Once extracted from profile extruders or compression mold presses, the finished composite parts can be either air or water cooled to ambient temperature prior to handling, storage, shipment or use.

The present invention is demonstrated by the following non-limiting examples.

Table I

Sample	1	2	3	4	5	6	7	8	9	10	11	12
Ingredients (wt %)												
Southern Pine ¹	30		30	30		30	30					
Southern Pine ²					30							
Poplar ³								30				
Poplar ⁴									30			
Poplar ⁵												30
Polyethylene ⁶	35	50	33.5	32	30	32.5	30	30	30	100		30
Polyethylene ⁷	35	50	33.5	32	30	32.5	30	30	30		100	30
Maleic Polypropylene ⁸			3	6								
Maleic Polyethylene ⁹						5						
Ethylene Methacrylic ¹⁰					10		10	10	10			10
Total	100	100	100	100	100	100	100	100	100	100	100	100

1. Virgin Southern Pine thermo-mechanical pulp, 5 percent moisture content, fiber size expressed by grind distribution as a percentage by weight of which 13 to 18 percent greater than eight mesh screen, 60 to 77 percent finer than eight mesh screen but greater than fifty mesh screen, and 5 to 27 percent finer than fifty mesh screen.
2. Virgin Southern Pine thermo-mechanical pulp, 5 percent moisture content, fiber size expressed by grind distribution as a percentage by weight of which 50 percent greater than eight mesh screen, 20 percent finer than eight mesh screen but greater than sixteen mesh screen, 20 percent finer than sixteen mesh screen but greater than fifty mesh screen, and 10 percent finer than fifty mesh screen.
3. Virgin Poplar thermo-mechanical pulp, 5 percent moisture content, fiber size expressed by grind distribution as a percentage by weight of which 13 to 18 percent greater than eight mesh screen, 60 to 77 percent finer than eight mesh screen but greater than fifty mesh screen, and 5 to 27 percent finer than fifty mesh screen.
4. Virgin Poplar thermo-mechanical pulp, 5 percent moisture content, fiber size expressed by grind distribution as a percentage by weight of which 50 percent greater than eight mesh screen, 20 percent finer than eight mesh screen but greater than sixteen mesh screen, 20 percent finer than sixteen mesh screen but greater than fifty mesh screen, and 10 percent finer than fifty mesh screen.
5. Virgin Poplar kiln dried wood waste, 5 percent moisture content, fiber size expressed by grind distribution as a percentage by weight of which 50 percent greater than eight mesh screen, 20 percent finer than eight mesh screen but greater than sixteen mesh screen, 20 percent finer than sixteen mesh screen but greater than fifty mesh screen, and 10 percent finer than fifty mesh screen.
6. Recycled polyethylene 0.34 lbs/in³ density, 6.925 gm/10 min. melt flow rate per ASTM D 1238.
7. Recycled polyethylene 0.34 lbs/in³ density, 0.70 gm/10 min. melt flow rate per ASTM D 1238.
8. Epolene G3003 by Eastman Chemical Company.
9. Polybond 3009 by Uniroyal Chemical Corporation.
10. Crystalene by Apex Specialty Polymers, Ltd.

The discontinuous lignocellulose fiber filler samples were prepared by conditioning wood chips from the listed sources in a pressure vessel for a period of between one and four minutes at a pressure of 80 psi to 100 psi. The conditioned chips were conveyed by screw conveyor at 65 psi to 85 psi to a Sunds Model 36-inch Defibrator and defibrated to the selected fiber size and fiber grind distribution. The discontinuous lignocellulose fibers were oven-dried to a moisture content of about 5 percent by weight.

All composite samples were prepared by blending the discontinuous lignocellulose fiber filler with thermoplastic, with or without coupling agents, at the concentrations listed in Table I in a low-shear mechanical mixing device. All samples were extruded through a Sterling six-inch bore extruder with a 34:1 screw compression ratio at 400°F, with the exception of Sample 6 which was extruded through a ZSK 30 millimeter twin screw extruder at 374°F. The extruded composite compositions were cold compression molded into test plaques. Test plaque mold temperatures ranged between 70°F and 100°F. Mold cycle times were three minutes. All test plaques were aged a minimum of seventy-two hours prior to testing.

Table II

ASTM Test	Performance Property	Sample 2	Sample 10	Sample 11
790-96	Flexural Strength (MPa)	14.5	16.1	12.3
790-96	Flexural Modulus (MPa)	680	640	460
256-93	Notched Izod (J/M)	154.9	49.3	174
638-96	Tensile @ Break (MPa)	18.6	11.6	15.4

Table II shows the physical properties of the thermoplastic samples.

Table III

ASTM Test	Performance Property	Sample 1	Sample 2
790-96	Flexural Strength (MPa)	23.8	14.5
790-96	Flexural Modulus (MPa)	1,288	680

Table III shows the improvement in flexural properties gained with the incorporation of the Southern Pine discontinuous lignocellulose reinforcing fiber filler at a concentration of 30 percent by weight into waste polyethylene without the use of coupling or bonding agents (Sample 1) over a polyethylene thermoplastic (Sample 2). The Sample 1 composition would be sufficient for applications requiring an improvement in stiffness over a thermoplastic.

Table IV

ASTM Test	Performance Property	Sample 1	Sample 2	Sample 3	Sample 4	Sample 6	Sample 7
790-96	Flexural Strength (MPa)	23.8	14.5	34	34.4	41.3	29
790-96	Flexural Modulus (MPa)	1288	680	1845	1871	1916	1390
638-96	Tensile @ Break (MPa)	14.6	18.6	21.5	19.9	33.1	17.8

Table IV shows the improvement in tensile and flexural properties of discontinuous lignocellulose fiber thermoplastic compositions with the addition of maleic anhydride grafted polypropylene (Samples 3 and 4), maleic anhydride grafted polyethylene (Sample 6) and ethylene methacrylic (Sample 7) coupling agents. With polyethylene as the base resin, the

composite with maleic anhydride grafted polyethylene (Sample 6) demonstrated superior performance over similar composites with maleic anhydride grafted polypropylene (Samples 3 and 4). The composite with ethylene methacrylic as the coupling agent (Sample 7) did not demonstrate the same rate of improved tensile and flexural properties obtained with like composites consisting of maleated polypropylene and maleated polyethylene as coupling agents. Increasing the content of maleic anhydride grafted polypropylene from 3 to 6 percent by weight of the composite compositions, as in Samples 3 and 4, yielded little if any gain in the performance of the composite.

Table V

ASTM Test	Performance Property	Sample 5	Sample 7	Sample 8	Sample 9	Sample 12
790-96a	Flexural Modulus (MPa)	1,476	1,390	1,464	1,625	1,573
638-96	Tensile @ Break (MPa)	19.1	17.8	22.7	23.9	24.6
256-93a	Notched Izod (J/M)	42.6	48.6	39.9	42.4	45.9

Table V shows the performance of composite samples having the same concentration of discontinuous lignocellulose cellulose fiber filler, but with varying concentrations of long fibers. The results indicate that, regardless of the tree species, as the percentage of discontinuous lignocellulose fibers with lengths in excess of fifteen millimeters was increased from 18 to 50 percent by weight within the polyethylene composite, the tensile properties of the composite improved. This improvement in tensile properties of the composite compositions with the greater percentage of long discontinuous lignocellulose fibers demonstrates that the long fibers of the discontinuous lignocellulose fiber filler of the present invention provide superior tensile properties over shorter fibers and particles.

Table V also shows that virgin wood fibers derived from softwood and hardwood species resulted in molded discontinuous lignocellulose fiber thermoplastic composite compositions with different properties. The composites including hardwood-derived fiber have superior tensile and flexural properties while the composites including softwood-derived fiber have superior Izod properties. Sample No. 7 derived from Southern Pine yields a composite with lower tensile

(strength) and flexural (stiffness) properties, but greater Izod (impact) properties than Sample No. 9 which is an identical composition derived from Poplar.

Sample 12 demonstrates the comparable performance of discontinuous lignocellulose fiber thermoplastic composites wherein the fiber is derived from virgin kiln dried hardwood waste.

Sample Nos. 7 and 9 were cold compression molded into cable reel flanges measuring 36 inches in diameter by 1.5 inches in width. In destructive drop testing, the cable reel flanges produced according to the present invention withstood a 48" vertical drop carrying 700 pounds of cable without fracturing, fatigue or failure. Thus, in a practical application the present invention derived from virgin wood has demonstrated its ability to overcome the brittleness typical of wood filled thermoplastic compositions.

The previously described embodiments of the present invention have many advantages, including providing a discontinuous lignocellulose fiber reinforcing filler for thermoplastic composite compositions which significantly improves the tensile and flexural properties of the composite. Such improvement is comparable to that obtained by other moldable compositions including the more-expensive chemical thermo-mechanical hardwood pulp. However, the present invention's use of thermo-mechanical pulp discontinuous lignocellulose fiber is more cost effective than using chemical thermo-mechanical discontinuous cellulose pulp with similar tensile property performance. Moreover, the source of the component materials of the composite composition may be waste wood and recycled thermoplastic, and the processes for manufacturing the fiber filler and composite are conventional. Thus, the present invention is a significant advance in thermoplastic composite technology in terms of both cost and performance.

While the present invention has been described in considerable detail in connection with preferred embodiments thereof, it will be understood, of course, that I do not intend to limit the invention to those embodiments since modifications may be made by those skilled in the art, particularly in light of the foregoing teachings. For example, numerous combinations of wood fiber sources and thermoplastic are possible within the scope of the disclosure. It is intended to cover all alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims. It is, therefore, contemplated to cover

by the appended claims any such modifications as incorporate those features which constitute the essential features of these improvements within the true spirit and the scope of the invention.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2